



Ultra A+ Server AS -2024US-TRT

2U Ultra with 12 SATA bays and 4 PCIe 3.0 x16 slots



Key Applications

Virtualization, Cloud Computing, High End Enterprise Server, Hyperconverged Storage, Flexible Networking Options,


Key Features

- Dual AMD EPYC™ 7003/7002 Series Processors
(The latest AMD EPYC™ 7003 Series Processor with AMD 3D V-Cache™ Technology requires BIOS version 2.3 or newer);
- 8TB Registered ECC DDR4 3200MHz SDRAM in 32 DIMMs;
- 2 PCIe 4.0 x16 (FH, 10.5" L) slots,
1 PCIe 4.0 x16 (FH, 9.5" L) slot,
1 PCIe 4.0 x16 (LP) slot,
1 PCIe 4.0 x8 (FH, 9.5" L, in x16) slot,
1 PCIe 4.0 x8 (internal proprietary LP in x16) slot;
- Dual 10GBase-T LAN ports via Intel® X710-AT2;
- 12 SATA3 by default
or 8 SATA3 + 4 NVMe via optional tray
or 12 SAS3 via optional SAS kit;




Form Factor	2U Rackmount Enclosure: 437 x 89 x 723mm (17.2" x 3.5" x 28.46") Package: 626 x 261 x 1153mm (24.65" x 10.28" x 45.39")
Processor	Dual Socket SP3 AMD EPYC™ 7002/7003 Series Processors
GPU	Max GPU Count: Up to 2 double-width or 4 single-width GPUs Supported GPU: NVIDIA PCIe: T4, RTX A6000, RTX A5000, RTX A4000, RTX A2000, RTX 8000, RTX 6000, RTX 4000, A40, A16, A2, A100, A10 AMD PCIe: Instinct™ MI210, Instinct™ MI100
System Memory	Slot Count: 32 DIMM slots/8 Channels Max Memory (2DPC): Up to 8TB 3200MT/s ECC DDR4 RDIMM/LRDIMM
Drive Bays Configuration	Default: Total 12 bays • 12 front hot-swap 3.5" SATA drive bays Option A: Total 12 bays • 8 front hot-swap 3.5" SATA drive bays • 4 front hot-swap 3.5"/2.5" NVMe* drive bays Option B: Total 12 bays • 12 front hot-swap 3.5" SAS* drive bays (*NVMe/SAS support may require additional storage controller and/or cables, please see the optional parts list for details)
Expansion Slots	Default • 2 PCIe 4.0 x16 FH/10.5"L slots • 1 PCIe 4.0 x16 LP slot • 1 PCIe 4.0 x8 LP slot • 1 PCIe 4.0 x16 FH, 9.5"L slot • 1 PCIe 4.0 x8 (in x16) FH, 9.5"L slot
On-Board Devices	SATA: SATA (6Gbps) Chipset: System on Chip Network Connectivity: 2 RJ45 10GbE IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 3 USB 3.0 Type-A ports(Rear)

(Front View – System)



(Rear View – System)



System Cooling	Fans: Up to 4 heavy duty fans with optimal fan speed control
Power Supply	2x 1600W Redundant (1 + 1) Titanium Level (96%) power supplies
System BIOS	BIOS Type: AMI 32MB SPI Flash EEPROM BIOS Features: Plug and Play (PnP) USB Keyboard support ACPI 5.1 DMI 2.3 PCI 2.2 SMBIOS 3.1.1
Management	SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); OOB Management Package (SFT-OOB-LIC); SuperServer Automation Assistant (SAA) New!; IPMICFG; SMCIPMITool; IPMIView
PC Health Monitoring	Temperature: Monitoring for CPU and chassis environment CPU thermal trip support Thermal control for 8x Fan connectors I²C Temperature Sensing Logic FAN: Status monitor for speed control Pulse Width Modulated (PWM) fan connectors Up to 8-fan status tachometer monitoring Up to eight 4-pin fan headers CPU: Monitors CPU Core Voltages, +12V, +3.3V, +5V, +5V standby, 3.3V standby, VBAT CPU switching voltage regulator Other Features: Chassis Intrusion Detection Chassis Intrusion Header
Dimensions and Weight	Weight: Gross Weight: 72 lbs (32.7 kg) Net Weight: 36 lbs (16.4 kg) Available Color: N/A
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 70°C (-40°F to 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Motherboard	Super H12DSU-iN
Chassis	CSE-829U2TS-R1K62P3-T